TOOL SHED INC. EST. 1945 EQUIPMENT RENTALS

FORKLIFT PRE-RENTAL INSPECTION CHECKLIST

To be filled out by the Driver delivering this forklift and then attached to the original invoice. Inspect and then initial all items that pertain to the forklift you are delivering. Any item that does not pass this safety inspection must be corrected before this forklift can be operated.

INSPECTION		
Overhead guard	Nomo	Data
Hydraulic cylinders	Name	Date
Mast assembly	E #	Contract #
Lift chains and rollers	Equip#	Contract #
Tire pressure & condition	T. 1	
Forks	Fuel	Hours
LPG tank and locator pin		
LPG tank hose		
Fuel gauge		
Check the engine oil level		
Examine the battery	Gas / Propane V	Warehouse Forklift
Check the hood/seat latches		
Inspect the hydraulic fluid level		
Check the engine coolant level		
Check the transmission fluid level	2.5	
Check the belts	18	
Check for fuel, oil, or water leaks	/ /	
Fire Extinguisher (optional)		
Warning & Safety decals are legible	(24	
Operators Manual		
Operators Manual	A PARTY	The state of the s
		14
TECT ODED ATION		
TEST OPERATION Stagening	1000	
Steering		
Brakes & Parking brake		
Horn		
Backup Alarm		
Safety Belt		
Transmission		
Front, tail, and brake lights		
Check the operation of the mast & tilt		
Check the operation of side shift	_	
-	Remarks	
Driver's Signature		

WARNING LARGE WAREHOUSE FORKLIFT

Any piece of equipment can be dangerous if not operated properly. <u>YOU</u> are responsible for the safe operation of this equipment. The operator must carefully read and follow any warnings, safety signs and instructions provided with or located on the equipment. Do not remove, defeat, deface or render inoperable any of the safety devices or warnings on this equipment. If any safety devices or warnings have been removed, defeated, defaced, or rendered inoperable, <u>DO NOT USE THIS EQUIPMENT!!!</u>

REQUIRES GASOLINE OR PROPANE ONLY

Operating Weight 16,020 Lbs. Maximum Capacity 8,500 Lbs. at a 24" Load Center

WARNING: Operating, servicing, and maintaining this equipment can expose you to chemicals including engine exhaust, carbon monoxide and lead, which are known to the State of California to cause cancer and birth defects or other reproductive harm. To minimize your exposure, avoid breathing exhaust, do not idle the engine except as necessary, operate and service your equipment in a well-ventilated area and wear gloves or wash your hands frequently when servicing your equipment. For more information go to www.P65warnings.ca.gov

THIS LIFT IS NOT FOR USE ON ROUGH TERRAIN OR HILLS!

ROLLOVER HAZARD, this lift is for use on level compacted surfaces only! **Warning:** Misuse, operating when not level and overloading will cause this Lift to Rollover. The Equipment Protection Plan does not cover damage to the Backrest, Tires, or from Rollover. Customers are responsible for tow & recovery services should the Lift become stuck or rolled over. A Tool Shed does not provide any tow or recovery services.

<u>DO NOT</u> use the Fork Load Backrest to pull or push anything. It is designed strictly to stop the materials you are lifting from falling backwards. <u>DAMAGE TO THE FORK LOAD BACKREST IS NOT COVERED BY THE EQUIPMENT PROTECTION PLAN</u>

FORK EXTENSION

<<**WARNING>>>** This forklifts load capacity is rated at a 24" load center. Using Fork Extensions greatly reduces this capacity. Always center your load on the extensions and *Never lift with the extension's tips*. It will bend them, and the Equipment Protection Plan does not cover this item.

OPERATING INSTRUCTIONS

The *Operator's Manual* is located in the pouch behind the seat.

Before you operate this lift, read, understand, and obey all the safety rules and operating instructions in the Operator's Manual.

Always perform a pre-operation inspection and function test prior to use.

Drivers shall check the forklift at least once per shift, and if it is found to be unsafe the matter shall be reported immediately to **A TOOL SHED**, and the forklift cannot be used again until it has been made safe. Attention shall be given to the proper functioning of tires, horn, lights, brakes, parking brake, steering mechanism, and the lift system of the forklift.

PARKING

Never leave forklift unattended while engine is running. When leaving the forklift unattended, set the parking brake, bring the mast to the vertical position, put the forks flat on the ground and shut the engine off.

NEVER use the forks or any other non-OSHA approved device to lift personnel! **NO RIDERS** this is strictly a single seat, NO Passenger machine!

8,500 lbs. Max Capacity at 24" load center to 15' 6"

IMPORTANT SAFETY RULED TO FOLLOW

- 1. **ONLY** drivers authorized by the customer and trained in the safe operation of this forklift shall be permitted to operate it. Do not allow any other person to ride on the forklift under any circumstances. Forklifts are one-person machines.
- 2. Drivers shall check the forklift at least once per shift, and if it is found to be unsafe the matter shall be reported immediately to **A TOOL SHED**, and the forklift cannot be used again until it has been made safe. Attention shall be given to the proper functioning of tires, horn, lights, brakes, parking brake, steering mechanism, and the lift system of the forklift.
- 3. Always wear the seatbelt and only operate forklift when you are sitting in the operator's seat. Always wear eye protection!
- 4. Always wear proper personal safety gear called for by the job or working conditions.
- 5. Maintain a safe clearance from electrical power lines and avoid contact with any electrically charged conductor.
- 6. Do not travel on the edge of docks. Always maintain a safe distance from the edge of platforms and road shoulders.
- 7. Do not turn the forklift suddenly. It will cause it to roller over. **NEVER JUMP OFF** the forklift even if it seems that it will tip. Always do as follows. Stay in the operator's seat. Hold the steering wheel securely. Brace your legs. *If you jump off the forklift when it turns over, there is danger that you will be fatally crushed under the forklift.*
- 8. Always carry your load as low as possible. Do not drive forklift with the load raised more than 24" above ground.
- 9. Never leave forklift unattended while engine is running. When leaving the forklift unattended, set the parking brake, bring the mast to the vertical position, put the forks flat on the ground and shut the engine off 10. This forklift can be used indoors or outdoors. For indoor use be sure to operate it using propane and have adequate ventilation. Carbon monoxide is a poisonous deadly gas. The propane switch is located in the engine compartment.
- 11. Never hang anything from the Forks or Extensions; a Forklift is not a Crane.
- 12. Never use a Forklift to support a load. Forklifts are for loading, unloading, and placing loads only.

Traveling on slopes.

When Loaded: Always keep the load upgrade. Travel forward up the slope & in reverse down the slope. When Unloaded: Always keeps the forks downgrade. Travel in reverse up the slope & forward down the slope.

Do not turn, or travel across or at an angle on slopes. There is a danger the forklift will tip.

REFUELING & MAINTENANCE

Warning: The Customer is responsible for all damages resulting from lack of fuel or lubrication. Check the motor oil, coolant, and hydraulic oil every time you refuel the equipment.

REFUELING: Stop the engine and shut off electrical equipment while filling the fuel tank. Use extra caution when fueling a hot engine. Always ground the fuel nozzle against the filler neck to avoid sparks. NEVER SMOKE while handling fuels.

COOLING SYSTEM: Keep the radiator free of debris. If at any time the motor overheats, shut it off and call us immediately. **Danger:** *Never remove the radiator cap on a hot engine the liquid is under pressure, extremely hot and will cause serious burns.* Liquid cooling systems build up pressure, as the engine gets hot. Before removing the radiator cap, stop the engine and let the system cool. Remove the radiator cap only after the system is cold. For cooling systems with an overflow tank, the coolant can usually be checked at the tank without removal of the radiator cap.

Warning metal conducts electricity. Do Not use this Lift where it may come into contact with power lines or other electric circuts. Failure to comply to this warning will result in serious personal injury or death. Keep appropriate distances from High Voltage lines. Never use the Lift as a ground for welding.

If the person receiving this handout will not be the user of the equipment, forward these instructions to the operator. **IF** there is any doubt as to the operation or safety of the equipment,

DO NOT USE!!! CALL A TOOL SHED IMMEDIATELY!!!
FAILURE TO FOLLOW THESE INSTRUCTIONS COULD RESULT IN INJURY OR DEATH